




VIEWLOG Data Logger

 We are certified
ISO 9001
certificate no. 07110505
Quality Is Our Standard



VIEWLOG

The small and uncomplicated data logger for the storage of analogue and digital values

- analogue or digital input for the connection of any sensor
- possibility of event-controlled data acquisition
- easy installation and operation
- low maintenance
- life time of battery up to 10 years

Notebook



DATA RECORDING



VIEWLOG


- analogue or digital input for the connection of any sensor
- possibility of event-controlled data acquisition
- easy installation and operation
- low maintenance
- life time of battery up to 10 years



Technical Data:

| | |
|------------------------|--|
| Signal Inputs: | 1 analogue input or 1 digital input or 2 digital inputs |
| Display: | LCD |
| Memory: | Ring-Memory 32 kB (optional 64 kB) |
| Memory Mode: | normal (time base) event-controlled (threshold value or dynamic mode) |
| Measuring Interval: | from 10s up freely adjustable or event control |
| Power supply: | 3,6 V Lithium battery sufficient for approx. 10 years in case of 1 measurement per minute |
| Protection Class: | IP 20 |
| Operation Temperature: | -10°C up to 70°C |
| Software: | Operation/readout with WBedien (from Win 95 up) (Ascii-output possible) |

The right is reserved to change or amend the foregoing technical specification without prior notice.



SEBA HYDROMETRIE GmbH
Gewerbestr. 61a * D-87600 Kaufbeuren
Tel.: +49 (0)8341 / 9648-0
Fax.: +49 (0)8341 / 9648-48
E-Mail: info@seba.de
Internet: www.seba.de

represented by: