

wind



Model 91000

*Response***ONE**[™] Ultrasonic Anemometer

The YOUNG *ResponseONE™* Ultrasonic Anemometer is designed to reliably measure wind speed and direction. The *ResponseONE™* is wind tunnel calibrated and will accurately measure wind speeds up to 70 m/s (156 mph). The high sampling rate of the Model 91000 provides for fast response to changing wind conditions and wind data may be updated as fast as 10 times per second. An easy-to-use Windows setup program is provided with each sensor. The program allows the user to customize device settings such as sampling rates and communication parameters.

The compact IP-66 rated design features durable, corrosion-resistant construction. An integrated compass helps enable mobile applications (Models 91500 & 91500B). A variety of useful standard serial output formats are provided including SDI-12, NMEA, and ASCII text. The sensor installs on readily available 1 inch (IPS) pipe and wiring connections are made in a convenient weather-proof junction box. Special connectors and cables are not required. The Model 91000 is available in black or white.



Specifications

Wind Speed	Range:	0 – 70 m/s (156 mph)
	Resolution:	0.01 m/s
	Starting Threshold:	<0.01 m/s
	Accuracy:	±2% or 0.3 m/s (0 – 30 m/s) ±3% (30 – 70 m/s)
	Response Time:	<0.25 seconds
Wind Direction	Azimuth Range:	0 - 360 degrees
	Resolution:	0.1 degree
	Starting Threshold:	<0.01 m/s
	Accuracy:	±2 degrees
	Response Time:	<0.25 seconds
Electronic Compass (Models 91500 & 91500 B)	Range:	0 – 360 degrees
	Resolution:	1 degree
	Accuracy:	± 2.0 degrees
Serial Output (selectable)	Interface:	RS-232, RS-485/422, SDI-12
	Formats:	NMEA, SDI-12, ASCII (polled or continuous)
	Baud Rates:	1200, 4800, 9600, 19200 and 38400
	Wind Units:	m/s, knots, mph, kmph
	Output Update Rate:	0.1 to 10 HZ
Power	Voltage:	10 – 30 VDC
	Current:	7 mA @ 12 VDC typical, 80 mA max
General	Protection Class:	IP66
	EMC Compliance:	FCC Class A digital device, IEC Standard 61326-1
	Dimensions:	22.0 cm high x 13.5 cm wide
	Weight:	0.5 kg (1.1 lb)
	Shipping Weight:	1.4 kg (3.1 lb)
	Operating Temperature:	-40 to +60 °C
	Removable Bird Spikes:	Included



The *ResponseONE™* is compatible with a broad range of data loggers and displays, including the YOUNG Model 06206 Marine Wind Tracker.

 Complies with applicable CE directives.

Ordering Information

MODEL

ResponseONE™ Ultrasonic Anemometer – White **91000**

ResponseONE™ Weather Transmitter – White **91500**
w/Internal Compass

ResponseONE™ Ultrasonic Anemometer – Black..... **91000B**

ResponseONE™ Weather Transmitter – Black **91500B**
w/Internal Compass



R.M. YOUNG COMPANY
2801 Aero Park Drive
Traverse City, Michigan 49686 USA
TEL: (231) 946-3980 FAX: (231) 946-4772
E-mail: met.sales@youngusa.com
Web Site: www.youngusa.com

 **KRITech & Co sprl**
Meteorology - Hydrology - Air & Gasflow
Gewerbestrasse 1 – B 4731 Raeren
Tel. +32 (0)87 85 04 78 – info@kritech.be