

wind

# *Serial Output Wind Sensor*



Model 09101  
**Wind Monitor-SE**

*The Wind Monitor-SE combines the performance and durability of our standard Wind Monitor with a unique optical encoder direction transducer and serial output.*

The Wind Monitor-SE offers maximum versatility in a conventional wind sensor. An optical encoder is utilized for vane angle measurement, thereby eliminating the characteristic deadband and wear of potentiometer transducers. The serial output signal is ideal for interfacing with modern data acquisition systems.

The wind speed sensor is a four blade helicoid propeller that turns a multi-pole magnet. Propeller rotation induces a variable frequency signal in a stationary coil; movable slip rings and brushes are not used. The raw signal is converted to a digital serial output by the on-board microprocessor circuit. A more conventional voltage output may be selected simply by moving an internal jumper.

The wind direction sensor is a durable molded vane. Vane angle is detected by a custom optical encoder. The encoder is an absolute type so direction output remains accurate even if power is interrupted. As with wind speed, a serial output or voltage output signal can be selected.

The Wind Monitor-SE is designed for superior environmental resistance. Housing parts are UV stabilized thermoplastic. Fittings are stainless steel and anodized aluminum. Precision grade stainless steel ball bearings are used throughout.

The instrument mounts on standard 1 inch pipe.



## Specifications

### Range:

Wind speed: 0-100 m/s (224 mph)  
Wind direction: 0-360 degrees

### Resolution:

Wind speed: 0.1 unit (m/s, kts, mph, km/h)  
Wind direction: 1 degree

### Accuracy:

Wind speed:  $\pm 0.3$  m/s (0.6 mph) or 1% of reading  
Wind direction:  $\pm 2$  degrees

### Dynamic Response:

Damping ratio: 0.3  
Damped natural wavelength: 7.4 m (24.3 ft)  
Undamped natural wavelength: 7.2 m (23.6 ft)

### Threshold:\*

Propeller: 1.0 m/s (2.2 mph)  
Vane: 1.1 m/s (2.5 mph)

### Available Outputs:

Voltage Output:  
WS: 0-5 VDC for 0-100 m/s  
WD: 0-5 VDC for 0-540°  
Serial RS-485:  
RMY, NCAR, or NMEA protocols  
Polled or continuous output

### Power Requirement:

11-24 VDC, 20 mA

### Dimensions:

Overall height: 37 cm (14.6 in)  
Overall length: 55 cm (21.6 in)  
Propeller: 18 cm (7.0 in) diameter  
Mounting: 34 mm (1.34 in) diameter (standard 1 inch pipe)

### Weight:

Sensor weight: 1.0 kg (2.2 lbs)  
Shipping weight: 2.3 kg (5 lbs)

### Operating Temperature:

-50 to 50° C

*\*Nominal values, determined in accordance with ASTM standard procedures.*

## Ordering Information

## MODEL

WIND MONITOR-SE ..... 09101

**CE** Complies with applicable CE directives.  
Specifications subject to change without notice.



### R.M. YOUNG COMPANY

2801 Aero Park Drive  
Traverse City, Michigan 49686 USA  
TEL: (231) 946-3980 FAX: (231) 946-4772  
E-mail: met.sales@youngusa.com  
Web Site: www.youngusa.com

Instruments for:  
METEOROLOGY  
HYDROLOGY  
WATER QUALITY  
AIR QUALITY  
INDOOR CLIMATE  
VENTILATION



KRITECH & Co PGmbH  
Gewerbestr. 1  
B - 4731 Raeren

Tel. 087 85 04 78  
Fax. 087 85 31 84  
E-Mail: [info@kritech.be](mailto:info@kritech.be)  
[www.kritech.be](http://www.kritech.be)